



# FUEL SAVING CONCEPT

**DEOFINE SUPER Oil** is formulated from quality base stocks combined with the most modern performance additives, including an advanced detergent system to provide excellent engine cleanliness.

These oils protect against sludge and engine rust and corrosion under low-temperature operating conditions.

Pour depressants and a viscosity index (VI) improver are included, where required, to provide the desired viscosity-temperature and low-temperature fluidity characteristics.

**DEOFINE SUPER Oil** is available in multi-viscosity grades:

**DEOFINE SUPER Oil** contain friction-reducing additives.

These viscosity grades are classified by the American Petroleum Institute (API) as "Energy Conserving" engine lubricants, and meet ILSAC GF-4, API : CH4,CI4,CL4,SM

# ILSAC GF-4 CH4,CI4,CL4 SM

- ♦ Excellent engine cleanliness
- ♦ Engine protection under a wide variety of operating conditions
- ♦ Fuel Saving Concepts
- ♦ Excellent protection for high-performance engines
- ♦ Helps reduce engine wear and corrosion    Helps keep engine clean
- ♦ Easy cold starting

SAE viscosity Grade	10W-40	15W-40	20W-50
Density @15 °C	0.88	0.88	0.89
Kinematic Viscosity @ 40 °C, cSt	97	148	162
Kinematic Viscosity @ 100 °C, cSt	12	14.83	18.1
Pour Point, °C	-33	-27	-20
High Temperature and High shear Viscosity 150 °C, 106s-1, mPa.S	3.35	4.12	4.86
TBN, mgKOH/g	10.7	11	10.9

